

TECHNICAL DATA SHEET

Intellivue MX550 Basic

Type	: Intellivue MX550 Basic
Parameter	: NBP, SpO2, HR, RR, Temp
COO	: Germany
Screen size (apprx)	: 15 inch widescreen
Size (W x H X D) in mm (apprx)	: (15.9 x 12.1 x 7.5 in) 6.25 mm/s, 12.5 mm/s, 25 mm/s, 50 mm/s
Display Rate	: with $\pm 5\%$ accuracy (guaranteed only for integrated displays)
Screen	: Touchscreen Display
Weight (apprx.)	: 7.5 kg (16.5 lb)
Waves	: 6 waveform
Battery (apprx)	: Basic monitoring configurations 2.5 hours
Smart key	: Yes
Trend review	: MX500/550: 4h@12s, 24h@1min, 48h@5min for 100 numerics
Standard measurement	: ECG/NIBP/RESP/ SPO2/TEMP
ECG	: ECG 5 lead, include EASI Method
RESP	: Impedancemetry lead II or lead I
SpO2	: FAST SpO2
NIBP	: Oscillometric with sequence mode and venous puncture
Temperature	: Yes
Accessories (for adult by default)	
SPO2 sensor	1
ECG cable	1
Temperature probe	1
NIBP cuff	1