

## TECHNICAL DATA SHEET

### Intellivue MX750 Advance

|                                       |  |
|---------------------------------------|--|
| Type                                  | : Intellivue MX750   |
| Parameter                             | : NBP, SpO2, HR, RR, Temp, IBP, EtCO2, CO                        |
| COO                                   | : Germany  |
| Screen size (apprx)                   | : 19 inch widescreen   |
| Size (W x H X D) in mm (apprx)        | : (18.8 x 13.8 x 8.5 in)   |
| Display Rate                          | : 469 mm active matrix color LCD (TFT)                           |
| Screen                                | : Touchscreen, 1920 x 1080 (Full HD)                             |
| Weight (apprx.)                       | : 10 kg (22. lb)   |
| Waves                                 | : > 8 waveform   |
| Smart key                             | : Yes  |
| Trend review                          | : 50 or 100 numerics @ 12 seconds, 1 minute, 5-minute resolution |
| Standard measurement                  | : ECG/NIBP/RESP/ SPO2/TEMP/IBP/EtCO2/CO                          |
| ECG                                   | : ECG 5 lead, include EASI Method                                |
| RESP                                  | : Impedancemetry lead II or lead I                               |
| SpO2                                  | : FAST SpO2  |
| NIBP                                  | : Oscillometric with sequence mode and venous puncture           |
| Temperature                           | : Yes  |
| IBP                                   | : Yes  |
| EtCO2                                 | : Mainstream   |
| CO                                    | : Yes  |
| Special Feature                       | : AD 75  |
| Accessories<br>(for adult by default) |  |
| SPO2 sensor                           | 1  |
| ECG cable                             | 1  |
| Temperature probe                     | 1  |
| NIBP cuff                             | 1  |
| Mainstream sensor                     | 1  |