

TECHNICAL DATA SHEET

Intellivue MX750 Anesthesia

Type	: Intellivue MX750
Parameter	: NBP, SpO2, HR, RR, Temp, IBP, EtCO2, Gas Module
COO	: Germany
Screen size (apprx)	: 19 inch widescreen
Size (W x H X D) in mm (apprx)	: (18.8 x 13.8 x 8.5 in)
Display Rate	: 469 mm active matrix color LCD (TFT)
Screen	: Touchscreen, 1920 x 1080 (Full HD)
Weight (apprx.)	: 10 kg (22. lb)
Waves	: > 8 waveform
Smart key	: Yes
Trend review	: 50 or 100 numerics @ 12 seconds, 1 minute, 5-minute resolution
Standard measurement	: ECG/NIBP/RESP/ SPO2/TEMP/IBP/EtCO2/Gas Module
ECG	: ECG 5 lead, include EASI Method
RESP	: Impedancemetry lead II or lead I
SpO2	: FAST SpO2
NIBP	: Oscillometric with sequence mode and venous puncture
Temperature	: Yes
IBP	: Yes
Gas Module	: Yes
Accessories (for adult by default)	
SPO2 sensor	1
ECG cable	1
Temperature probe	1
NIBP cuff	1